

FibeAir IP-20GX

Rev. A.02 | October 2017
ETSI Version



General

Assembly options

Two expansion slots for any combination of:

- Radio Modem Cards (RMC) – RMC-B
- TDM Line Cards (LIC):
 - TDM – LIC-T16 (16x E1)
 - TDM – LIC-T155 (1x ch-STM-1)

Radio

Supported Frequency Range

6-42 GHz

Radio Configurations

1+0, 2+0 SP/DP, 4+0, 1+1 HSB, 4 x 1+0

Radio Features

Multi-Carrier Adaptive Bandwidth Control (up to 2+0)

Protection and Diversity: HSB, SD (BBS)

High spectral utilization: QPSK to 2048 QAM w/ACM

XPIC

Ethernet

Ethernet Interfaces

2 x 10/100/1000Base-T Electrical (RJ-45)

2 x 10/100/1000Base-T Dual Mode Electrical or Cascading (RJ-45)

2 x 1000base-X (SFP)

Management Interfaces – 2 x 10/100 Base-T (RJ-45)

SFP Types - Optical 1000Base-LX (1310 nm) or SX (850 nm)

Ethernet Features

MTU – 9600 Bytes

Quality of Service

- Multiple Classification criteria (VLAN ID, P-bits, IPv4 DSCP, IPv6 TC, MPLS EXP)
- 8 priority queues per port
- Deep buffering (configurable up to 64 Mbit per queue)
- WRED
- P-bit marking/remarking

4K VLANs

VLAN add/remove/translate

MSTP, ERP (ITU-T G.8032)

Frame Cut Through – controlled latency and PDV for delay sensitive applications

Header DeDuplication – Capacity boosting by eliminating inefficiency in all layers (L2,MPLS, L3,L4, Tunneling – GTP for LTE, GRE)

Y.1731 Ethernet OAM

TDM

TDM Interfaces

16 x E1s (optional)

TDM Features

Fixed interface: 16 x E1s

Expansion Slots (Optional): 2 x LIC-T16 (16xE1) and/or LIC-T155 (1xch-STM-1)

Synchronization

Synchronization Distribution

Sync Distribution over any traffic interface (GE/FE, E1*, STM-1)

Dedicated In/Out synch interface (E1/2 MHz)†

SyncE (ITU-T G.8261, G.8262)

SSM/ESMC Support for ring/mesh applications (ITU-T G.8264)

SyncE Regenerator mode, providing PRC grade (ITU-T G.811) performance for smart pipe applications

IEEE-1588

Optimized Transport for reduced PDV

IEEE-1588 TC

IEEE-1588 BC

* Planned for future release.

† Input via the synch interface is planned for future release.



Standards

MEF

Carrier Ethernet 2.0 (CE 2.0)

Supported Ethernet Standards

10/100/1000base-T/X (IEEE 802.3)

Ethernet VLANs (IEEE 802.3ac)

Virtual LAN (VLAN, IEEE 802.1Q)

Class of service (IEEE 802.1p)

Provider bridges (QinQ – IEEE 802.1ad)

Link aggregation (IEEE 802.3ad)

Auto MDI/MDIX for 1000baseT

RFC 1349: IPv4 TOS

RFC 2474: IPv4 DSCP

RFC 2460: IPv6 Traffic Classes

Supported E1 Standards

ITU-T G.703, G.736, G.775, G.823, G.824, G.828, ITU-T I.432, ETSI ETS 300 147, ETS 300 417

Supported STM-1 Standards

ITU-T G.703, G.775, G.813, G.825, EN 300 386 V1.2.1, ES 201 468; V1.1.1 :2000-03, ES 201 468 V1.2.1 :2002-09, EN 61000 4-3

TDM Pseudowire Standards

SAToP – RFC 4553

Security

Radio Encryption – AES 256

Secured protocols:

- HTTPS
- SNMPv3
- SSH
- SFTP

RADIUS authentication and authorization

Standards Compliance

Radio Spectral Efficiency: EN 302 217-2-2

EMC: EN 301 489-4, EN 301 489-1, FCC 47 CFR, part 15, class B

Safety: EN 60950-1, IEC 60950-1, UL 60950-1, CSA-C22.2

No.60950-1, EN 60950-22, UL 60950-22, CSA C22.2.60950-22

Ingress Protection: IEC 60529 IP56

Storage: ETSI EN 300 019-1-1 Class 1.2

Transportation: ETSI EN 300 019-1-2 Class 2.3

Technical Specifications

Mechanical Specifications

IDU: 44mm(H), 426mm(W), 180mm(D), 2.5kg

Plugin Card Weight: 0.5kg

Fans Drawer Weight: 0.3 kg

RFU-C – 200mm(H), 200mm(W), 85mm(D), 4kg;

1500HP/RFU-HP – 490mm(H), 144mm(W), 280mm(D), 7kg(W) (excluding Branching)

1500HP/RFU-HP OCB Branching (Split Mount and Compact All-Indoor) – 420mm(H), 110mm(W), 380mm(D), 7kg per carrier

Environmental Specifications

IDU: -5° to +55°C (-25°C to +65°C extended);

RFU: -33°C to +55°C (-45°C to +60°C extended)

Power Input Specifications

IDU Standard Input: -48 VDC

IDU DC Input range: -40 to -60 VDC

Dual-feed power support

Power Consumption Specifications

IDU with full assembly (expansion slots not populated): ~48W

Addition per RMC in expansion slot: 17W

Addition per LIC-T16 (16xE1) in expansion slot: 17W

Addition per LIC-T155 (1x ch-STM-1) in expansion slot: 25W

RFU-C – 6-26 GHz (1+0/1+1): 22W/39W; 28-42 GHz (1+0/1+1): 26W/43W

RFU-HP (6-8 GHz) – Max Bias: 73W; Mid Bias: 48W; Min Bias: 34W; Mute: 18W

RFU-HP (11 GHz) – Max Bias: 74W; Mid Bias: 64W; Mute: 21W

1500HP – Max Bias: 85W; Mid Bias: 72W; Mute: 29W



Product Images

IDU

IP-20GX IDU



Modules

PLUGIN CARDS – RADIO MODEM CARDS (RMCs)



PLUGIN CARDS – 16 x E1/1 x CH-STM-1 INTERFACES



Radio Units

RFU-C



1500HP/RFU-HP



Radio Specifications

Capacity and Maximum Number of E1s

Notes: For full specifications, please contact your Ceragon sales representative.

	Capacity (Mbps)	Capacity De-Dup	Max. No. of E1s	Capacity (Mbps)	Capacity De-Dup	Max. No. of E1s	Capacity (Mbps)	Capacity De-Dup	Max. No. of E1s
Modulation	3.5 MHz			7 MHz			14 MHz		
QPSK	3-4	4-13	2	8-10	9-32	4	19-24	20-74	9
8 PSK	-	-	-	13-16	13-48	6	29-36	31-112	13
16 QAM	8-10	9-32	4	18-22	19-69	8	40-49	42-153	18
32 QAM	11-14	12-43	5	24-30	26-92	11	53-65	56-203	24
64 QAM	14-17	15-54	6	30-37	32-114	14	66-80	69-249	29
128 QAM	17-21	18-65	8	36-44	38-137	16	79-97	83-301	36
256 QAM	19-24	20-74	9	42-51	44-158	19	90-110	95-344	41
512 QAM	-	-	-	45-54	47-169	20	100-122	105-380	45
1024 QAM Strong	-	-	-	48-58	50-182	21	106-129	111-402	48
1024 QAM Light	-	-	-	51-62	53-194	23	112-137	118-426	50
Modulation	28 MHz			40 MHz			56 MHz		
QPSK	43-52	45-162	19	58-71	61-220	26	87-106	91-331	39
8 PSK	62-76	65-236	28	86-105	90-328	39	127-155	133-482	57
16 QAM	87-107	92-332	39	117-143	123-446	53	176-215	185-670	79
32 QAM	115-140	121-437	52	154-189	162-588	69	232-283	243-881	104
64 QAM	141-173	149-538	64	190-232	199-722	85	284-348	299-1000	128
128 QAM	170-208	179-648	77	229-280	241-873	103	344-420	361-1000	155
256 QAM	196-239	206-745	88	247-302	259-939	111	397-485	416-1000	178
512 QAM	209-255	219-794	94	270-330	284-1000	122	427-521	448-1000	192
1024 QAM Strong	228-278	239-866	102	306-375	322-1000	138	464-567	487-1000	209
1024 QAM Light	241-295	253-917	108	325-398	342-1000	146	493-602	517-1000	222
2048 QAM	263-321	276-1000	118	352-430	370-1000	158	534-653	561-1000	240

Transmit Power

Transmit Power (dBm)	Frequency (GHz)	6-8	11-15	18-23	24	26	28	31	32	36	38	42
QPSK/8 PSK		33	29	22	0	21	14	16	18	12	18	15
16 QAM		33	29	21	0	20	14	15	17	11	17	14
32 QAM		33	29	20	0	19	14	14	16	10	16	13
64 QAM		33	29	20	0	19	14	14	16	10	16	13
128 QAM		32	28	20	0	19	14	14	16	10	16	13
256 QAM		31	27	18	0	17	12	12	14	8	14	11
512 QAM		29	25	18	-1	17	9	12	14	10	14	11
1024 QAM		28	25	17	-3	16	8	11	13	9	13	10
2048 QAM		26	23	15	0	14	6	9	11	7	11	8



Receiver Threshold (RSL) (dBm @ BER = 10⁻⁶)

3.5 MHz	Frequency (GHz)	6	7-10	11-15	18	23	24	26	28	31-42
3.5 MHz										
QPSK		-97.5	-97.0	-97.5	-96.5	-96.0	-93.0	-95.0	-93.0	-94.0
16 QAM		-91.0	-90.5	-91.0	-90.0	-89.5	-86.5	-88.5	-86.5	-87.5
32 QAM		-88.0	-87.5	-88.0	-87.0	-86.5	-83.5	-85.5	-83.5	-84.5
64 QAM		-84.5	-84.0	-84.5	-83.5	-83.0	-80.0	-82.0	-80.0	-81.0
128 QAM		-81.0	-80.5	-81.0	-80.0	-79.5	-76.5	-78.5	-76.5	-77.5
256 QAM		-77.5	-77.0	-77.5	-76.5	-76.0	-73.0	-75.0	-73.0	-74.0
7 MHz										
QPSK		-95.0	-94.5	-95.0	-94.0	-93.5	-90.5	-92.5	-90.5	-91.5
8 PSK		-89.0	-88.5	-89.0	-88.0	-87.5	-84.5	-86.5	-84.5	-85.5
16 QAM		-88.5	-88.0	-88.5	-87.5	-87.0	-84.0	-86.0	-84.0	-85.0
32 QAM		-85.0	-84.5	-85.0	-84.0	-83.5	-80.5	-82.5	-80.5	-81.5
64 QAM		-82.0	-81.5	-82.0	-81.0	-80.5	-77.5	-79.5	-77.5	-78.5
128 QAM		-79.0	-78.5	-79.0	-78.0	-77.5	-74.5	-76.5	-74.5	-75.5
256 QAM		-75.5	-75.0	-75.5	-74.5	-74.0	-71.0	-73.0	-71.0	-72.0
512 QAM		-73.5	-73.0	-73.5	-72.5	-72.0	-69.0	-71.0	-69.0	-70.0
1024 QAM Strong		-70.0	-69.5	-70.0	-69.0	-68.5	-65.5	-67.5	-65.5	-66.5
1024 QAM Light		-69.5	-69	-69.5	-68.5	-68.0	-65.0	-67.0	-65.0	-66.0
14 MHz										
QPSK		-92.0	-91.5	-92.0	-91.0	-90.5	-87.5	-89.5	-87.5	-88.5
8 PSK		-86.0	-85.5	-86.0	-85.0	-84.5	-81.5	-83.5	-81.5	-82.5
16 QAM		-85.0	-84.5	-85.0	-84.0	-83.5	-80.5	-82.5	-80.5	-81.5
32 QAM		-82.0	-81.5	-82.0	-81.0	-80.5	-77.5	-79.5	-77.5	-78.5
64 QAM		-79.0	-78.5	-79.0	-78.0	-77.5	-74.5	-76.5	-74.5	-75.5
128 QAM		-75.5	-75.0	-75.5	-74.5	-74.0	-71.0	-73.0	-71.0	-72.0
256 QAM		-73.0	-72.5	-73.0	-72.0	-71.5	-68.5	-70.5	-68.5	-69.5
512 QAM		-70.0	-69.5	-70.0	-69.0	-68.5	-65.5	-67.5	-65.5	-66.5
1024 QAM Strong		-67.0	-66.5	-67.0	-66.0	-65.5	-62.5	-64.5	-62.5	-63.5
1024 QAM Light		-66.5	-66.0	-66.5	-65.5	-65.0	-62.0	-64.0	-62.0	-63.0
28 MHz										
QPSK		-89.0	-88.5	-89.0	-88.0	-87.5	-84.5	-86.5	-84.5	-85.5
8 PSK		-84.5	-84.0	-84.5	-83.5	-83.0	-80.0	-82.0	-80.0	-81.0
16 QAM		-82.5	-82.0	-82.5	-81.5	-81.0	-78.0	-80.0	-78.0	-79.0
32 QAM		-79.0	-78.5	-79.0	-78.0	-77.5	-74.5	-76.5	-74.5	-75.5
64 QAM		-76.0	-75.5	-76.0	-75.0	-74.5	-71.5	-73.5	-71.5	-72.5
128 QAM		-72.5	-72.0	-72.5	-71.5	-71.0	-68.0	-70.0	-68.0	-69.0
256 QAM		-69.5	-69.0	-69.5	-68.5	-68.0	-65.0	-67.0	-65.0	-66.0
512 QAM		-67.5	-67.0	-67.5	-66.5	-66.0	-63.0	-65.0	-63.0	-64.0
1024 QAM Strong		-64.5	-64.0	-64.5	-63.5	-63.0	-60.0	-62.0	-60.0	-61.0
1024 QAM Light		-63.5	-63.0	-63.5	-62.5	-62.0	-59.0	-61.0	-59.0	-60.0
2048 QAM		-60.0	-59.5	-60.0	-59.0	-58.5	-55.5	-57.5	-55.5	-56.5



40 MHz									
QPSK	-87.5	-87.0	-87.5	-86.5	-86.0	-80.5	-85.0	-83.0	-84.0
8 PSK	-82.5	-82.0	-82.5	-81.5	-81.0	-75.5	-80.0	-78.0	-79.0
16 QAM	-81.0	-80.5	-81.0	-80.0	-79.5	-74.0	-78.5	-76.5	-77.5
32 QAM	-77.5	-77.0	-77.5	-76.5	-76.0	-70.5	-75.0	-73.0	-74.0
64 QAM	-74.5	-74.0	-74.5	-73.5	-73.0	-67.5	-72.0	-70.0	-71.0
128 QAM	-71.5	-71.0	-71.5	-70.5	-70.0	-64.5	-69.0	-67.0	-68.0
256 QAM	-69.0	-68.5	-69.0	-68.0	-67.5	-62.0	-66.5	-64.5	-65.5
512 QAM	-66.5	-66.0	-66.5	-65.5	-65.0	-59.5	-64.0	-62.0	-63.0
1024 QAM Strong	-63.5	-63.0	-63.5	-62.5	-62.0	-56.5	-61.0	-59.0	-60.0
1024 QAM Light	-62.5	-62.0	-62.5	-61.5	-61.0	-55.5	-60.0	-58.0	-59.0
2048 QAM	-59.0	-58.5	-59.0	-58.0	-57.5	-52.0	-56.5	-54.5	-55.5
56 MHz									
QPSK	-85.5	-85.0	-85.5	-84.5	-84.0	-81.0	-83.0	-81.0	-82.0
8 PSK	-81.5	-81.0	-81.5	-80.5	-80.0	-77.0	-79.0	-77.0	-78.0
16 QAM	-79.0	-78.5	-79.0	-78.0	-77.5	-74.5	-76.5	-74.5	-75.5
32 QAM	-75.5	-75.0	-75.5	-74.5	-74.0	-71.0	-73.0	-71.0	-72.0
64 QAM	-72.5	-72.0	-72.5	-71.5	-71.0	-68.0	-70.0	-68.0	-69.0
128 QAM	-69.5	-69.0	-69.5	-68.5	-68.0	-65.0	-67.0	-65.0	-66.0
256 QAM	-66.5	-66.0	-66.5	-65.5	-65.0	-62.0	-64.0	-62.0	-63.0
512 QAM	-64.5	-64.0	-64.5	-63.5	-63.0	-60.0	-62.0	-60.0	-61.0
1024 QAM Strong	-61.0	-60.5	-61.0	-60.0	-59.5	-56.5	-58.5	-56.5	-57.5
1024 QAM Light	-60.0	-59.5	-60.0	-59.0	-58.5	-55.5	-57.5	-55.5	-56.5
2048 QAM	-55.5	-55.0	-55.5	-54.5	-54.0	-51.0	-53.0	-51.0	-52.0

